

StreetRap

PRODUCT DESCRIPTION

White matt calendered PVC film specially designed for bitumen applications, outdoor sidewalk and parking lot floor graphics.

Face material:

70 µm white matt polymeric PVC

Adhesive:

Solvent acrylic high-tack transparent adhesive

Liner:

PE coated 165 g/sqm

TYPICAL USE

Short-term promotional graphics on outdoor flat surfaces. Almost anywhere you have pedestrian traffic, StreetRap can present your message to customers, clients, visitors and employees: Fairs, Trade Shows, Retail outlets, Convention Centers, Public buildings, Safety messages, Schools, Sport or Entertainment venues.

PROCESSING

Especially designed for solvent based, eco-solvent, mild solvent and Latex printing on wide-format printing equipment.

StreetRap is intended to be laminated in combination with FloorGrip for flat applications or StreetLam for conformable and highly durable floor graphics.

To achieve the best possible print quality, please make sure that the correct printer settings are used. For further information, please refer to TB 4.1 "Guidelines on handling, converting and applying Mactac Digital media."

SHELF LIFE

2 years when stored at 15 to 25°C and ± 50 % relative humidity (in the original packaging).

APPLICATION METHOD

Mactac Digital media must be applied following the instructions in TB 4.1 "Guidelines on handling, converting and applying Mactac Digital media", available from the resource section at www.mactacgraphics.eu.

To ensure application suitability, always test the proposed construction under actual application and end-use conditions before going into full production.

PHYSICAL PROPERTIES (TYPICAL VALUES)

Adhesive data, 23°C (N/25 mm)	Average values	Test method
-------------------------------	----------------	-------------

Quick tack on stainless steel:	22.1	FTM 9
Peel 24 hours on stainless steel:	20.6	FTM 1

Dimensional stability

Shrinkage (48 hours at 70°C applied on aluminium)	Max. 1.0 mm	FTM 14
---	-------------	--------

Temperature ranges

Minimum application temperature	+ 10°C
Service temperature range of use	-20°C to +70°C

Certifications

Fire certification	Self-extinguishing
--------------------	--------------------

EXPECTED DURABILITY*

Central Europe Zone 1

Unprocessed	1 year	ISO 4892-2.
Printed and applied	6 months	ISO 4892-2.

Note : Exposure to severe temperatures, ultraviolet light, and/or conditions in Southern European countries, tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high altitudes and south-facing exposure. No durability warranty is given for horizontal exposure.

Important notice: Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Disclaimer and warranty: Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

ALPHASET
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.
Kopčianska 19, 851 01 Bratislava
tel: +421 2 6381 2255
mobil: +421 918 656 524
e-mail: alphaset@alphaset.sk

