

Non-curl Grey Back PET banner

Item	Unit	Value	Test Method	
Support Cloth	Polyethylene Terephthalate (PET)			
Thickness of PET	Micron	125	/	
Coating	PVC			
Total weight	gsm/m2	330±20	DIN53352 BS3424 Method5A	
Width	m	0.914, 1.07, 1.27, 1.37, 1.52, 2.20, 2.50, 3.20		
Tensile Strength	N/5cm	Warp	1182	DIN53354 BS3424 Method6A
		Weft	1173	
Tearing Strength	N/5cm	Warp	34	DIN53356 BS3424 Method7A
		Weft	27	
Temperature Resistance	°C	-20~70	DIN53357 BS3425 Method10	
Flammability	B1, B2, M2, NFPA701, etc (on options)			
Ink Printability	Solvent, Eco-solvent, UV and Screen Printing			
Advantages	<ul style="list-style-type: none"> ◆ Super smooth surface for high resolution printing. ◆ Grey back and opaque. ◆ Non-curling at the edge and lay-flat appearance. ◆ No lamination needed. 			
Applications	<ul style="list-style-type: none"> ◆ Display system, Roll-up, Pop-up, X-Banner, Scrolling banner ◆ Hanging graphics for exhibitions, retail display, corporate events 			

ALPHASET
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.
Kopčianska 19, 851 01 Bratislava
tel: +421 2 6381 2255
mobil: +421 918 656 524
e-mail: alphaset@alphaset.sk

