

PET-Grey-330

Non-curl Grey Back PET banner

Item	Unit	Value	Test Method
Support Cloth	Polyethylene Terephthalate (PET)		
Thickness of PET	Micron	125	/
Coating	PVC		
Total weight	gsm/m2	330±20	DIN53352 BS3424 Method5A
Width	m	0.914, 1.07, 1.27, 1.37, 1.52, 2.20, 2.50, 3.20	
Tensile Strength	N/5cm	Warp	1182
		Weft	1173
Tearing Strength	N/5cm	Warp	34
		Weft	27
Temperature Resistance	°C	-20~70	DIN53357 BS3425 Method10
Flammability	B1, B2, M2, NFPA701, etc (on options)		
Ink Printability	Solvent, Eco-solvent, UV and Screen Printing		
Advantages	<ul style="list-style-type: none"> ◆ Super smooth surface for high resolution printing. ◆ Grey back and opaque. ◆ Non-curling at the edge and lay-flat appearance. ◆ No lamination needed. 		
Applications	<ul style="list-style-type: none"> ◆ Display system, Roll-up, Pop-up, X-Banner, Scrolling banner ◆ Hanging graphics for exhibitions, retail display, corporate events 		
Statement	All technical information herein is based on tests by UNISIGN Technical Laboratory.		