

SBP25 display film 420g

Description: High-quality frontlit PET display film with a gray back for high opacity

Application: For roll-up displays and display graphics.

Characteristics: The SBP25 has a good flatness, is scratch-proof, tear-resistant and opaque due to the gray back. The product is B1 certified.

Inks and printers:Universally applicable for printers with solvent, UV-curing inks and latex inks

Oppression: Before printing, acclimatize the material to room temperature (> 20°C) in the printer room for at least 2 hours. Ensure a dust-free printing environment and avoid fingerprints on the printing surface by wearing cotton gloves. Make sure the device and temperature settings are correct using a test print. Depending on the printing process chosen and the ink limit set, we recommend laying the film flat after printing until it has finally dried.

Storage: After each use, store the material immediately after printing to avoid contamination and curling. Pack the material back into the protective film and store the roll upright in a light-protected and dust-free environment at 40 to 60% relative humidity and 15 to 25°C room temperature.

Technical Data:

Characteristic	Value	method
Weight	420gsm	DIN 53352
Temperature range	- 20°C - +70°C	DIN 53372
Fire protection certificate	B1	

Hints: The technical data refers to the unprinted material. Our information does not release you from carrying out your own tests to check suitability for your application. We have no influence on the properties and durability of the inks; please also note the printer manufacturer's instructions. The data sheet is based on manufacturer information; Alphaset assumes no liability. Subject to technical changes and typesetting errors. June 2023 version

ALPHASET
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.
 Kopčianska 19, 851 01 Bratislava
 tel: +421 2 6381 2255
 mobil: +421 918 656 524
 e-mail: alphaset@alphaset.sk

