

SPN120 poster paper neon yellow, 120g

- Description:** High-quality satin-finished coated yellow fluorescent paper
- Application:** Posterprinting for indoor and outdoor use, promotional purposes
- Characteristics:** The SPN120 impresses with its excellent paper stability and fast drying time. It is ideal for promotional materials and is also PEFC™ 100% certified.
- Inks and printers:** Universally applicable for printers using solvent, eco-solvent, UV and latex inks
- Oppression:** Before printing, acclimatize the material to room temperature (>20°C) for at least 2 hours in the printer room. The print side should be facing outwards. Ensure a dust-free printing environment and avoid fingerprints on the print surface by wearing cotton gloves.
- Storage:** Store the material immediately after printing to prevent contamination and warping. Repack the material in the protective film and store the roll upright in a light-protected and dust-free environment at 40 to 60% relative humidity and 18 to 25°C room temperature. Shelf life is 12 months.

Technical Data:

Characteristic	Value	method
Grammar	120g	ISO 536
thickness	124µm	ISO 534
smoothness	Top 42 sec Back 44 sec	ISO DP 5627

Dimension:

Length, roller core	60 linear meters wound on a 3-inch core
Widths	1270 mm

- Printing recommendations:** Print direction: Bi-directional
Resolution: 720x1080dpi (6-12 passes)
Color coverage: 120-180%
Printing speed: 10-12 m²/h Drying
temperature: 40-35-40°

Notes:

The technical data refers to the unprinted material. Our information does not relieve you of the responsibility to conduct your own tests to verify suitability for your application. We have no control over the properties and durability of the inks; please also refer to the printer manufacturer's instructions. This data sheet is based on manufacturer specifications; Alphaset accepts no liability. Technical specifications and typographical errors excepted. Version September 2021