

**SPP120 Blueback poster paper, 130g**

**Description:** Satin coated wet strength paper with blue backing

**Application:** Indoor and outdoor poster advertising.

**Characteristics:** The SPP120 impresses with its excellent image quality, high and very good scratch and fold resistance without whitening. The blue backline ensures high opacity of the paper. The product is environmentally friendly and recyclable (FSC certified).

**Inks and printers:**Universally applicable for printers with solvent, eco-solvent and UV-curing inks

**Oppression:** Before printing, acclimatize the material to room temperature (> 20°C) in the printer room for at least 2 hours. The print side is on the outside. Ensure a dust-free printing environment and avoid fingerprints on the printing surface by wearing cotton gloves.

**Lamination:** Suitable for cold lamination up to 60°C. Please make sure that the print has dried thoroughly before laminating (recommendation 24 hours with the paper lying open).

**Placarding:** The paper is wet-strength, weather-resistant and ideal for posters. The expected lifespan of a billboard is 3 months. The material was tested by APG.

**Storage:** After printing, store the material immediately to avoid contamination and curling. Pack the material back into the protective film and store the roll upright in a light-protected and dust-free environment at 30 to 65% relative humidity and 10 to 30°C room temperature. The shelf life is 12 months.

**Technical Data:**

Characteristic	Value	method
total weight	130gr	ISO536
thickness	150µm	ISO534
opacity	>98%	ISO2471
Gloss (85°)	51°	ISO2813
Color (D50/2°)	L*94.3a*1.3b*-4.4	ISO13655

**Dimension:**

Length, roll core	61 linear meters wound on 3 inch core
widths	914mm, 1067mm, 1270mm, 1372mm, 1600mm

**Hints:**

The technical data refers to the unprinted material. Our information does not release you from carrying out your own tests to check suitability for your application. We have no influence on the properties and durability of the inks; please also note the printer manufacturer's instructions. The data sheet is based on manufacturer information; Alphaset assumes no liability. Subject to technical changes and typesetting errors. Version September 2021

**ALPHASET**  
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.  
Kopčianska 19, 851 01 Bratislava  
tel: +421 2 6381 2255  
mobil: +421 918 656 524  
e-mail: alphaset@alphaset.sk

