

SPS151 Premium paper, semi-matte, 150 g

- Description:** Coated paper, semi-matte
- Application:** Indoor advertising, also for backlit and city light applications
- Characteristics:** The paper is quick-drying and boasts excellent image quality, good flatness, and good scratch and fold resistance without whitening. The product is environmentally friendly and recyclable (FSC-certified).
- Inks and printers:** Universally applicable for printers using solvent, eco-solvent, latex and UV-curing ink
- Oppression:** Before printing, acclimatize the material to room temperature (> 20°C) for at least 24 hours in the printer room. The print side should be facing outwards. Ensure a dust-free printing environment and avoid fingerprints on the print surface by wearing cotton gloves.
- Lamination:** Suitable for cold lamination up to 60°C. Please ensure that the print is thoroughly dry before laminating (24 hours recommended with the paper laid flat).
- Storage:** Store the material immediately after printing to prevent contamination and warping. Repack the material in the protective film and store the roll upright in a light-protected and dust-free environment at 30 to 65% relative humidity and 10 to 30°C room temperature. Shelf life is 12 months.

Technical Data:

Characteristic	Value	method
Total weight	150 g/m ²	
thickness	150 µm	
opacity	> 96%	
Color (120 CIE)	L*94.7 a*1.8 b*-7.5	

- Notes:** The technical data refers to the unprinted material. Our information does not relieve you of the responsibility to conduct your own tests to verify suitability for your application. We have no influence on the properties and durability of the inks; please also refer to the printer manufacturer's instructions. This data sheet is based on manufacturer specifications; Alphaset accepts no liability. Technical specifications and typographical errors excepted. MR 03 2026