## **Datenblatt**

## **ALPHASET**

## STP50 textile banner PES fabric

Description: Bright white satin, universally applicable PES fabric with special

polymer coating for solvent printing, flame retardant B1

Application: Textile decorations of the highest quality, e.g. trade fair construction, banners, stage and

wall decorations, frame systems, clamping systems, frontlit, displays, ceiling constructions and much more. Also suitable for short-term outdoor use (except printing with latex inks).

Inks and printers: Universally applicable with solvent ink or eco-solvent ink as well as UV printers and latex

inks

Oppression: The medium is – like all print media – sensitive to fingerprints. Contact with the surface

to be printed must be avoided. Print side is on the outside.

Particularities: Highest print quality, no whitening, waterproof and water-repellent, dirt-

repellent, can be cut cold without fraying

Technical Data:

Characteristic	Value	method
material	100% polyester	DIN 60001
binding	tissue	DIN ISO 9354
Weight per unit area	200 g/m² (+/- 10)	DIN EN ISO 2286-2
Fire behavior	Yes	DIN 4102 B1; ÖNORM A3800; NFPA 701; CA 1237

**Dimensions:** 

Length, roll core	30 running meters
widths	1100mm, 1370mm, 1620mm

Hints:

The technical data refers to the unprinted material. Our information does not release you from carrying out your own tests to check suitability for your application. We have no influence on the properties and durability of the inks; please also note the printer manufacturer's instructions. The data sheet is based on manufacturer information; Alphaset assumes no liability. Subject to technical changes and typesetting errors. Version September 2021



ALPHASET spol. s r.o. Kopčianska 19, 851 01 Bratislava tel: +421 2 6381 2255 mobil: +421 918 656 524 e-mail: alphaset@alphaset.sk

