

BALACRON

DIGIMEDIA

Product datasheet

Collection : Wall Media
Design : DigiFort P300
Product description : Paper backed vinyl print media

Composition		Dimensions	Test method
Total weight	300 ± 15	gsm	ISO 2286-2
Weight Paper	90 ± 15	gsm	
Weight coating*	210 ± 15	gsm	
Roll width	1300	mm	
Roll length	50	meter	
Internal core diameter	76	mm	
Packaging	Kraft paper		

*Vinyl base coating with specially formulated acrylic topcoating with exclusive inkjet receptive properties.

Product features prior to printing

Suitable printing inks	Latex, Eco-solvent, Solvent, UV-curable
Resistant to	Soap; detergents; alcohol; ammonia; alkali; diluted acids
Non resistant to	Solvents like ketones; esters; aromatic hydrocarbons
Washability	Extra scrubbable - EN 259-1 / EN12956
Lightfastness	≥ 7 International Woolscale - BS EN 20105 / ISO EN 105-B02
FSC	FSC certified: FSC-C141806
Reach	Reach compliant according to EU regulation 1907/2006EC
Non-Phthalate	Yes
Made in EU	CE Compliant according to EN 15102:2007 + A1:2011
	Details see Declaration of Performance 09

Fire safety

Euroclass	B-s2-d0	EN13501-1
Germany	B1	DIN4102-1

Application instruction

Adhesives	Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute
-----------	--

Product sheet last revised: 03-12-2020

ALPHASET
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.
Kopčianska 19, 851 01 Bratislava
tel: +421 2 6381 2255
mobil: +421 918 656 524
e-mail: alphaset@alphaset.sk



Balacron DigiMedia
Rokerijweg 5
1271 AH Huizen
The Netherlands

Tel +31 35 524 84 25
Mail info@balacron.com
Web www.balacron.com

