

Media Datasheet SCM-GPPM

Photo Paper Matt

Description:

Roland SCM-GPPM is a 265 grams photo paper with a special coating developed for Roland EcoSol-Max Inks. This high quality photo paper has a white matt PE-coated surface, provided with a special one-sided printable coating. High detail and vibrant images are printed in combination with Roland EcoSol-Max inks.

Physical Properties:

Paper weight	(paper+ coating)	265 grams/m ²
Gloss rate	(ISO 8254/1)	33 %

Product line:

	Length	Width
SCM-GPPM-40-762	40m	760mm
SCM-GPPM-40-107	40m	1067mm
SCM-GPPM-40-127	40m	1270mm

Typical Uses:

SCM-GPPM is developed indoor applications such as:

- Digital high quality photo prints
- Interior decorations
- Exhibition & fairs
- Point of sale advertising
- Short term outdoor
- ...

Ideal for all your high quality prints on glossy paper.

Benefits:

Roland DG's experience with digital printers enables the launch of a media portfolio focused on outstanding image performance and ease-of-use in together with Roland DG equipment.

- Excellent price / performance ratio for high quality promotional graphics.
- Thanks to the special coating, SCM-GPPM can be used for indoor as well as short term outdoor applications.
- This thicker paper combines easy handling with a professional result.

Material processing and handling

This material is especially designed for Roland DG eco-solvent printing equipment.

To achieve the best possible print quality, please make use of the profiles and settings developed by Roland DG. Profiles can be obtained **free of charge** from our certified dealer network or can be directly downloaded from:

<http://www.rolandmediacenter.eu>

It is imperative to set up the printer correctly and that the correct profile and heater settings are used. Do not handle the face film directly and ensure it is free from dust and static.

We advise you to leave the prints to dry sufficiently before rolling them or laying them on top of each other.

Recommendations

- Shelf Life

Two years when stored at 15°C to 25°C and 50% relative humidity (in the original Roland packaging).

- Printing Conditions

Air-conditioned printroom, $\pm 23^{\circ}\text{C}$ and 50 % R.H.

- Transportation conditions

We advise you to leave the prints to dry sufficiently before rolling them or laying them on top of each other.

Important

All Roland DG products are subject to careful quality control. Information on physical and chemical characteristics is based upon tests we believe to be reliable for West European exposure conditions. The values listed herein are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All specifications are subject to change without prior notice. All technical data are subject to change. In case of any ambiguities or differences between the English version and version in any other language of these Conditions, the English version shall be controlling.

Warranty

Roland DG branded media are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorized to give any guarantee, warranty or make any representation contrary to the foregoing. All Roland DG branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

ROLAND DG BENELUX N.V. | Houtstraat 3, B-2260 OEVEL (WESTERLO) | Media@rolanddg.eu | www.rolandmediacenter.eu

ALPHASET
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.
Kopčianska 19, 851 01 Bratislava
tel: +421 2 6381 2255
mobil: +421 918 656 524
e-mail: alphaset@alphaset.sk

