

Fredrix



ARCHIVAL
**PRINT
CANVAS**

PRODUCT SPECIFICATION SHEET INKJET PRINTING CANVASES

PRODUCT NAME: **ARTISAN**, 901 Semi-Gloss SJ
ITEM MASTER: 131 + Width

CANVAS CONSTRUCTION: 65% polyester/ 35% cotton base, 2 x 1 Weave

COATING: Two Acrylic Latex Primer Basecoats
Semi_Gloss Solvent Receptive Topcoat

ACIDITY (pH): Neutral (Acid-free)

APPEARANCE: White, with medium texture

FINISH WEIGHT: 11.25 osy \pm 1.25 osy
381 gsm \pm 43 gsm

THICKNESS: 17.75 mils \pm 1.25 mils
451 microns \pm 32 microns

COLOR: (X-Rite 938 Spectrodensitometer, D₅₀²)

Whiteness	81.00 minimum
Brightness	84.00 minimum
L	91.00 minimum
a	0.00 nominal
b	0.00 nominal

SPECTRAL GLOSS, 60°: 5.0 nominal
(Byk-Gardner Micro Tri-gloss)

This canvas is designed for digital printing applications using solvent based ink sets. Although designed for all printers using these ink sets, actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F \pm 5°F and relative humidity of 50% RH \pm 3% RH.

Tara Materials guarantees only the canvas itself against defects in quality or workmanship. No other warranty is expressed or implied.

ALPHASET
TECHNOLÓGIE A MATERIÁLY NA VÝROBU REKLAMY

ALPHASET spol. s r.o.
Kopčianska 19, 851 01 Bratislava
tel: +421 2 6381 2255
mobil: +421 918 656 524
e-mail: alphaset@alphaset.sk



Web:

WWW.FREDRIXPRINTCANVAS.COM

ALL PRODUCTS ARE MANUFACTURED IN THE USA